


# R165

# SKID LOADERS



**GEHL**®

Capacities		Metric	Imperial
Rated Operating Capacity		748 kg	1649 lb
Rated Operating Capacity with Optional Counterweight		816.50 kg	1800 lb
Unladen weight		2796 kg	6164 lb
Weight and dimensions			
Overall Operating Height - Fully Raised	h27	3876 mm	153 in
Height to Hinge Pin – Fully Raised	h28	3018 mm	119 in
Overall Height to Top of ROPS	h17	1956 mm	77 in
Dump angle at full height	a5	38 °	38 °
Dump height	h29	2379 mm	94 in
Overall length with bucket	l16	3101 mm	122 in
Dump reach - Full height	r6	579 mm	23 in
Rollback at ground		28 °	28 °
Seat to ground height	h30	904 mm	36 in
Wheelbase	y	986 mm	39 in
Overall width less bucket	b1	1580 mm	62 in
Bucket Width	e1	1562 mm	61 in
Ground clearance	m4	160 mm	524 ft 11 in
Overall length - Less Bucket	l2	2385 mm	94 in
Departure angle	a2	21 °	21 °
Clearance Radius - Front with Bucket	b18	1869 mm	74 in
Clearance Circle - Front without Bucket	b19	1153 mm	45 in
Clearance Circle - Rear	wa1	1466 mm	58 in
Performances			
Travel Speed with Two-Speed Option - Maximum		19.50 km/h	12 mi/h
Travel speed (unladen)		12.60 km/h	8 mi/h
Wheels			
Standard tyres		10.00x16.5 HD	10.00x16.5 HD
Engine			
Engine brand		Yanmar	Yanmar
Engine model		4TNV98C-NMS2V Stage V	4TNV98C-NMS2V Stage V
Engine norm		Stage V	Stage V
Gross Power (kW)		51.70 kW	51.70 kW
Net Power (kW)		51 kW	51 kW
Max. torque / Engine rotation		241 Nm / 2500 rpm	241 Nm / 2500 rpm
Battery		12 V	12 V
Starter (kW)		2.30 kW	2.30 kW
Hydraulics			
Standard flow - Auxiliary hydraulics		77 l/min	77 l/min
High-Flow Auxiliary Hydraulics – Option		114 l/min	114 l/min
Tank capacities			
Fuel tank		62.50 l	17 US gal
Reservoir Capacity Hydraulics		39 l	10 US gal
Displacement		3.30 l	0.87 US gal
Noise and vibration			
Environmental noise (LwA)		101 dB	101 dB
Whole-Body Vibration (ISO 2631-1)		1.05 m/s <sup>2</sup>	1.05 m/s <sup>2</sup>
Vibration to whole hand/arm		< 1.53 m/s <sup>2</sup>	< 1.53 m/s <sup>2</sup>



# GEHL®

Siège Social  
P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095  
Tel: (262) 334-9461 - Fax: (262) 338-7517  
[www.gehl.com](http://www.gehl.com)



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend